

# TC-610

## Professional Two-way Radio

Harsh, noisy and dusty working conditions in mega-project and construction sites may lower your efficiency and productivity by smudging the radio or shadowing the talk. HYT TC-610 portable radio is the option customized for users in these industries, as its superior dust & water protection performance helps to

- Dust/Water Protection Class IP66
- Powerful Audio and Wide Communication Range
- Reliable Mechanical Design
- Innovative Industrial Design





# TC-610

## Professional Two-way Radio

### Super Features

#### Dust/Water Protection Class IP66

In harsh, noisy and dusty working conditions such as construction sites and engineering sites, your radio is apt to be smudged. The TC-610 portable radios are IP66-rated and have excellent dust/water protection performance. The IP66 protection allows you to wash off mud and dust on your radio. A water jet (40mm  $\varnothing$ ) from a nozzle, which is projected from any direction against your radio for up to one minute, must not have any harmful effect. Your radio could be dried to operate normally after you wash it.

#### Powerful Audio and Wide Communication Range

Superior audio quality is the premise for your team to work efficiently in noise environments. A powerful speaker with size of 45mm  $\varnothing$  (36mm  $\varnothing$  speaker for common radios) ensures clear and crisp sound, even in noisy environments. You can also use high transmit power for wide communication coverage.

#### Reliable Mechanical Design

Battery latch is apt to become loose after long time use, and even occasionally causes your radio to shut off automatically. All these will affect your working efficiency. HYT proprietary battery latch mechanism is applied to TC-610 radios. It delivers secure connection between battery and radio, no matter how long the radio has been in use.

#### Innovative Industrial Design

The TC-610 abandons conventional black body, and employs fashionable yellow rubber housing, making the radio more comfortable to handle.

• IP66 water protection ensures the radio to be protected against a water jet for one minute. The diameter of the water jet is 40 mm.

## Main Features and Functions

### High/Low Power Switchable

By simple pressing one button, users can switch to low power when communicating within limited range coverage or switch to high power when further distance is required. High transmit power optimizes range coverage while low transmit power conserves battery consumption, all at the user's control.

### Programmable 12.5kHz / 25kHz Channel Spacing

The feature enables flexibility and easy migration of channel spacing requirements when the need arises, with no need to buy new radios.

### Monitor

Allows users to monitor the activity on the current channel. The feature is especially helpful for receiving a weak signal.

### Battery Save

The Battery Save feature is automatically activated once no activity on the channel and no operation performed, for extended operation time.

### Low Battery Alert

Alert users to recharge the battery should the battery level run low.

### Busy Channel Lockout

A channel already in use is not available to other users.

### Time-out Timer

The feature allows for more efficient use of channels by limiting the amount of time of each transmission.

### PC Programmable

You are able to customize the features of each radio for each user.

### Wired Clone

Easily copy the features of one radio to another.

### CTCSS/CDCSS

Set up workgroups/users with unique CDCSS/CTCSS to prevent unwanted conversations on the same frequency. ▶

### Selectable Squelch Level (0-9)

Helps minimize interference from undesired weak signals and helps weak signals be heard.

### Channel Scan

The channel scan feature enables the radio to continuously scan each channel in the scan list for activity. Simply press a side function button to activate scanning. When activity is detected on a channel the scan process will stop and you will hear the transmission.

### Voice Operated Transmit (VOX)

Enjoy the convenience of hands-free operation when used with optional accessories.

## Recommended Applications

- Construction sites
- Hotel
- Manufacturing
- Property management
- Ports
- Warehousing

## Accessories

### Standard Accessories

U/V Antenna    MCU Charger CH10A03    Belt Clip BC12    Li-ion Battery (1200mAh) BL1204  
Switching Power Adapter (different P/N for different countries and areas)    Strap RO03

### Optional Accessories



Li-ion Battery (2000mAh)  
BL2001



MCU Rapid-rate Multi-unit  
Charger for Li-ion/Ni-MH  
Batteries MCA02



Lightweight Single-muff  
Headset with in-line  
PTT & VOX  
ECM12




Earpiece with on-MIC  
PTT & VOX & Transparent  
Acoustic Tube EAM12  
2-Wire Surveillance Earpiece  
with VOX & Transparent  
Acoustic Tube (black)  
EAM13  
3-Wire Surveillance Earpiece  
with Transparent Acoustic  
Tube (black/beige)  
EAM16 / EAM15



Water Resistant Remote Speaker  
Microphone (IP56) SM13M1



Noise-cancelling Remote  
Speaker Microphone  
(350-390MHz) SM13M2



Remote Speaker  
Microphone SM08M3


Receive-only Earpiece with  
Transparent Acoustic Tube  
(for use with remote speaker  
microphone)  
ESS08

Receive-only Earbud  
(for use with remote speaker  
microphone)  
ESS07

2-wire Earpiece with  
Wireless Receiver and  
Neck Loop (Beige) EWM03




Behind-the-head,  
Noise-cancelling  
Headset ECM14




Heavy Weight  
Noise-cancelling  
Headset ECM13




Light Weight, Throat-  
vibrating Earpiece ELM01



Ear Canal Bone Induction  
Earpiece EBM01



D-earset with Boom  
Microphone & in-line  
PTT & VOX EHM16



D-earset with in-line  
PTT & Microphone & VOX  
EHM15



Universal Chest Pack  
(Nylon)(Black) LCBN13  
Leather Carrying Case  
(non-swivel)  
LCBN56



Earbud with in-line  
PTT & VOX ESM11  
Earbud with on-MIC  
PTT & VOX ESM12



## Applicable MIL-STD-810C/D/E/F

Applicable MIL-STD	810C Methods Procedures	810D Methods Procedures	810E Methods Procedures	810F Methods Procedures
Low Pressure	500.1 1	500.2 1,2	500.3 1,2	500.4 1
High Temperature	501.1 1,2	501.2 1,2	501.3 1,2	501.4 1,2
Low Temperature	502.1 1	502.2 1,2	502.3 1,2	502.4 1,2
Temp. Shock	503.1 1	503.2 1	503.3 1	503.4 1
Solar Radiation	505.1 1	505.2 1	505.3 1	505.4 1,2
Rain	506.1 2	506.2 2	506.3 1,2	506.4 1,2
Humidity	507.1 2	507.2 2,3	507.3 2,3	507.4 1

## General

Frequency Range(MHz)	VHF: 136-174 UHF: 400-420 440-470 420-450 450-470 420-470 470-490
Channel Capacity	16
Channel Spacing(KHz)	25 /12.5
Operating Voltage(V)	7.4
Battery	More than 9 hours 1200mAh (Li-ion)
Battery Life (5-5-90 Duty Cycle)	More than 9 hours
1200mAh Li-Ion battery	More than 14 hours ±2.5
1300mAh Ni-MH battery	-20~+55
2000mAh Li-Ion battery	50
Frequency Stability(ppm)	119×55×33

## Transmitter

Dimensions (H×W×D)(with battery, without antenna)(mm)	5W/2W(VHF) 5W/2W(UHF)
RF Power Output	
Weight (with antenna & battery)(g)	
Modulation	F3E
Spurious and Harmonics	-36dBm<1GHz -30dBm>1GHz
EM Noise	40/35dB

All Specifications are tested according to TIA/EIA-603, and subject to change without notice due to continuous development.

## Receiver

Sensitivity	0.25/0.28 μV
Selectivity	70/60dB
Intermodulation	≥65dB
Spurious Response Rejection	≥70dB
S/N	45/40dB



## Hytera Communications Corporation Limited

Address: Hytera Tower, Hi-Tech Industrial Park North, Beihuan Rd.,  
Nanshan District, Shenzhen, China

Tel: +86-755-2697 2999 Fax: +86-755-8613 7139 Post: 518057

Http: //www.hytera.com

Hytera retains right to change the product design and specification. Should any printing mistake occur, Hytera doesn't bear relevant responsibility. Little difference between real product and product indicated by printing materials will occur by printing reason.

Hytera are registered trademarks of Hytera Co., Ltd. © 2014 Hytera Co., Ltd. All Rights Reserved.

Your Local Dealer

