

General	
Frequency Range	UHF: 350-470MHz VHF: 136-174MHz
Channel Capacity	256
Zone Capacity	16
Channel Spacing	25/12.5KHz
Operating Voltage	7.4V
Battery	2000mAh (Li-Ion)
Battery Life (5/5/90)	Analog/Digital: 12/16 hours
Weight	308g
Dimensions	117×55×37mm
Frequency Stability	±0.5ppm
Antenna Impedance	50Ω
Receiver	
Sensitivity (Digital)	0.22μV / BER 5%
Sensitivity (Analog)	0.22μV (Typical) (12dB SIN AD) 0.4μV (20dB SIN AD) 0.22μV (12dB SIN AD)
Adjacent Selectivity	TIA-603 60dB @ 12.5KHz/70dB @ 25KHz
	ETSI 60dB @ 12.5KHz/70dB @ 25KHz
Spurious Response Rejection	TIA-603 70dB @ 12.5/25KHz
	ETSI 70dB @ 12.5/25KHz
Inter-modulation	TIA-603 70dB @ 12.5/25KHz
	ETSI 65dB @ 12.5/25KHz
Hum & Noise	40dB @ 12.5KHz 45dB @ 25KHz
Rated Audio Power Output	0.5W
Rated Audio Distortion	≤3%
Audio Response	+1 ~ -3dB
Conducted Spurious Emission	<-57dBm

Transmitter	
RF Power Output	VHF High power: 5W VHF Low power: 1W UHF High power: 4W UHF Low power: 1W
FM Modulation	11K0F3E @ 12.5KHz 16K0F3E @ 25KHz
4FSK Digital Modulation	12.5KHz Data Only: 7K60FXD 12.5KHz Data & Voice: 7K60FXW
Conducted/Radiated Emission	-36dBm <1GHz, -30dBm >1GHz
Modulation Limiting	±2.5KHz @ 12.5KHz ±5.0KHz @ 25KHz
FM Hum & Noise	40dB @ 12.5KHz 45dB @ 25KHz
Adjacent Channel Power	60dB @ 12.5KHz, 70dB @ 25KHz
Audio Response	+1 ~ -3dB
Audio Distortion	≤3%
Digital Vocoder Type	AMBE+2™
Digital Protocol	ETSI-TS102 361-1,-2,-3

Environmental	
Operating Temperature	-30°C ~ +60°C
Storage Temperature	-40°C ~ +85°C
ESD	IEC 61000-4-2 (Level 4) ±8kV (Contact) ±15kV (Air)
Dustproof & Waterproof	IP54 Standard
Humidity	Per MIL-STD-810 G Standard
Shock & Vibration	Per MIL-STD-810 G Standard

PD48X, X=0, 2, 5, 6 or 8, model number varies geographically. For details, please contact our regional sales representatives.
All specifications are subject to change without notice due to continuous development.



Digital Migration Radio PD48X

- 10 Clear Voice
- 10 Built-in Bluetooth & GPS(Factory)



Hytera retains right to change the product design and specification. Should any printing mistake occur, Hytera doesn't bear relevant responsibility. Little difference between real product and product indicated by printing materials will occur by printing reason.



Features

- PRIVACY**
Basic end-to-end Encryption has your voice and data
- DTMF SIGNALING**
- EMERGENCY ALARM/ CALL**
Emergency Alarm can be sent to other radios via one touch of programmable button, then establish an emergency call in a
- PSEUDO TRUNK**
This virtual trunking feature allocates a free timeslot for urgent communications. This effectively enhances frequency efficiency
- REAL TIME CLOCK**
- VOX**
This feature allows you to activate the radio microphone via
- RRS RADIO REGISTRATION SERVICE**
RRS allows PD48X working in Smart Dispatch and Smart One Dispatch, so that the dispatcher can check if the radio is on line
- SUPPLEMENTARY FEATURES (Optional)**
PD48X Series provide radio enable/disable, remoter monitor and
- ROAMING (Optional)**
Roam from each repeater site to have a non-stop voice
- GPS POSITIONING (Factory Optional)**
Built-in GPS module and GPS antenna are designed for outdoor positioning and make it very simple to support different kinds of
- BUILT-IN BLUETOOTH (Factory Optional)**
Built-in Bluetooth supports PD48X to have wireless audio
- RELIABLE AND DURABLE**

Target Markets



FLEET MANAGEMENT
With RRS, PD48X is allowed to be access to Dispatch application for fleet management. Get what you need for PD48X, like voice dispatch, text message or



COMMERCIAL
Digital clear voice and loud output audio for most situations with noisy environment in commercial event. With wireless earpiece and text message



SECURITY
Privacy in voice and data is the most essential for security guard. Emergency Call, Priority Interrupt, or Remote Monitor function provides a reliable



OUTDOOR ADVENTURES
Quite flexible to quickly program the radio through front panel. Got GPS position in real time. Based on military quality and IP54 water-proof, it is an amazing way

Standard



Options

